

HINIKER VF PLOW

9000 SERIES

Super-bright quad halogen headlights have up to twice the power of typical sealed beam lamps.

Moldboards flare out from 30 inches high at center to 37 inches (8½' plows) or 38 inches (9½' plows). The high curve high-density polyethylene moldboards are dent-free and corrosion-free. Snow flows easily for more efficient plowing. Optional rubber or polyethylene snow deflectors available.

High clearance trip-edges operate independently of one another, reducing stress and twisting forces on the plow.

6" high-carbon steel replaceable cutting edge.

Pinch-free pivot point is 9 inches above the surface providing protection from higher obstacles such as curbs and parking barriers.

One pass plowing . . . no problem! Hiniker's pitch adjustment levels the blade to assure full ground contact for optimum cleaning efficiency.

The high-tensile steel superstructure of the moldboard provides excellent resistance to bending and bowing, for extra heavy-duty applications. 12 laser-cut steel ribs add exceptional strength.

Long-lasting cast ductile-iron skid shoes.

Strength, Capacity, and Versatility

The new Hiniker 9000 Series V-Plows offer the versatility that only a V-Plow can, along with the strength and operator convenience that you've come to expect from Hiniker.

VF PLOW

- Exclusive high pivot point trip-edge
- Super-bright quad halogen lights
- Double acting hydraulic power



Double-acting cylinders provide positive hydraulic control of moldboard position, whether plowing forward or backdragging.

Convenient Command of all V-plow functions: Scoop, Vee, Angle Right, Angle Left, Raise and Lower.



Positive wing stops relieve stress on the hydraulic cylinders. 2-way cylinders provide precise moldboard control.



High-performance power units provide quick response & long-term reliability.

VF PLOW Specifications:

MODEL		9860	9960
BLADE WIDTH		8½'	9½'
CUTTING WIDTH	V-POSITION	93.5"	104"
	SCOOP	83.5"	94"
	STRAIGHT	102"	114"
	ANGLE	88.5"	99"
MOLDBOARD HEIGHT		30-37"	30-38"
MOLDBOARD SURFACE		¼" HMW poly	
TRIP PIVOT POINT HEIGHT		9"	
TRIP SPRINGS		4	
STANDARD CUTTING EDGE		⅝" X 6" High-Carbon Steel	
WEIGHT (NET OF TRUCK MOUNTED HARDWARE)		841 lb.	877 lb.



PUT SNOW IN ITS PLACE